

AIR SCREWDRIVERS, CLUTCH TYPE

For High Performance Fastening

* Capacity is listed as instant reference and depends on operation conditions.

MACHINE SCREW Dia. 2.6~3.5mm (7/64"-9/64")

GT-H4RC



Ball spring retainer
6,35mm




Noise reducer

OP Torque adjusting spring (medium / weak)

Accessories



Angle head size



MACHINE SCREW Dia. 3.5~4.5mm (9/64"-11/64")

GT-H5RC




Ball spring retainer
6,35mm



Accessories



Angle head size



MACHINE SCREW Dia. 3~4mm (1/8"-5/32")

GT-H4R



Ball spring retainer
6,35mm

Lever push starting / Noise reducer

OP Anvil for A/F 5mm bit
Torque adjusting spring (medium / weak)

Accessories



GT-H4PR



Ball spring retainer
6,35mm

Push startup type / Rear exhaust

OP Torque adjusting spring (medium / weak)

Accessories



GT-PH4



Ball spring retainer
6,35mm

Lever push starting
Noise reducer / Rear exhaust


OP Torque adjusting spring (medium / weak)

Accessories




Bit installation anvil application

Unless otherwise, following bit specification should be standardized.



Option : Following retainer anvil is available.



MACHINE SCREW Dia. 4~5mm (5/32"-3/16")

GT-H5R




Ball spring retainer
6,35mm

Lever push starting

Accessories



GT-H5P



Ball spring retainer
6,35mm

Push startup type / Rear exhaust

Accessories



GT-PH5



Ball spring retainer
6,35mm

Lever push starting
Noise reducer / Rear exhaust

Accessories



EDP No.	Model No.	Torque Range		Free Speed rpm	Air Consumption m ³ /min.	Overall length		Weight		Air hose Size	Body Form
		N. m	(ft. lbf)			mm	in.	g	lb.		
311036	GT-H4R	1.0-2.2	(0.7-1.6)	1,500	0.2	190	7 15/32	590	1.30	PF1/4	Straight
311046	GT-H4PR	1.0-2.2	(0.8-1.6)	1,500	0.19	213	8 3/8	610	1.34	PF1/4	Straight
311037	GT-PH4	1.0-2.2	(0.8-1.6)	1,500	0.19	180	7 3/32	800	1.76	PT1/4	Pistol
311034	GT-H4RC	0.5-1.8	(0.4-1.3)	1,500	0.2	216	8 1/2	900	1.98	PF1/4	Angle
311066	GT-H5R	2.0-5.4	(1.5-4.0)	1,500	0.25	225	8 27/32	880	1.94	PF1/4	Straight
311065	GT-H5P	2.0-5.4	(1.5-4.0)	1,500	0.25	235	9 1/4	880	1.94	PF1/4	Straight
311067	GT-PH5	2.0-5.4	(1.5-4.0)	1,500	0.25	200	7 7/8	1,070	2.36	PT1/4	Pistol
311064	GT-H5RC	1.0-3.0	(0.7-2.2)	1,500	0.25	248	9 3/4	1,190	2.62	PF1/4	Angle

* Air pressure...6kgf/cm² (85psi) * Air hose bore diameter ... 6.35mm (1/4") * Overall length ... Accessory, hanger part not included.
* Weight ...Accessories not included.

CAUTION! Please be sure to read through "For the safety use of the tools."