



Bearing No.	Boundary dimensions (mm)				Basic dynamic load rating Ca (N)	Maximum axial load (N)	Limiting speed (min ⁻¹)	Abutment and fillet dimensions (mm)				Pre-load (GM) (N)	
	D	B	r (min)	r ₁ (min)				d _{a1}	d _{a2}	D _{a1}	D _{a2}		
20TAB04DF-2LR 20TAB04DB-2LR	20	47	15	1	0.6	25,900	30,500	4,400	26.8	33.7	35	41.9	2,160
25TAB06DF-2LR 25TAB06DB-2LR	25	62	15	1	0.6	29,900	43,000	3,250	39.7	46.2	47.5	54.9	3,330
30TAB06DF-2LR 30TAB06DB-2LR	30	62	15	1	0.6	29,900	43,000	3,250	39.7	46.2	47.5	54.9	3,330
35TAB07DF-2LR 35TAB07DB-2LR	35	72	15	1	0.6	32,500	52,000	2,600	49.7	56.2	57.5	64.9	3,920
40TAB07DF-2LR 40TAB07DB-2LR	40	72	15	1	0.6	32,500	52,000	2,600	49.7	56.2	57.5	64.9	3,920
40TAB09DF-2LR 40TAB09DB-2LR	40	90	20	1	0.6	65,000	96,500	2,200	57.2	67.2	68.5	79.9	6,200