

Bottom Roller Bearings

Designation	Dimensions(mm)				Holder		Pin	Equivalent To	
	d	D	b	B	Type N	Type W	PD x L	INA	SKF
					Center	Side			
BR 2800	16.5	28	19	22	5.9	-	-	UWL 2800	-
BR 2820	16.5	28	19	22	-	20.2	-	UWL 2820	-
BR 2822	16.5	28	19	22	-	22.2	-	UWL 2822	-
BR 2824	16.5	28	19	22	-	24.2	-	UWL 2824	-
BR 282023	16.5	28	19	23	-	20.2	-	-	UL 28-0000416
BR 282223	16.5	28	19	23	-	22.2	-	-	UL 28-0000417
BR 282423	16.5	28	19	23	-	24.2	-	-	UL 28-0000418
BR 282623	16.5	28	19	23	-	26.2	-	-	UL 28-0010047
BR 282423X	16.5	28	23	23	-	24.2	-	-	UL 28-0010083
BR 28242326	16.5	28	23	26	-	24.2	-	-	-
BR 3000	18.5	30	19	22	5.9	-	-	UWL 3000	UL 30-0007871
BR 3020	18.5	30	19	22	-	20.2	-	-	-
BR 3022	18.5	30	19	22	-	22.2	-	-	UL 30-0002610
BR 3200	19	32	20	23	5.9	-	-	UWL 3200	-
BR 3220	19	32	20	23	-	20.2	-	UWL 3220	-
BR 3222	19	32	20	23	-	22.2	-	UWL 3222	-
BR 3224	19	32	20	23	-	24.2	-	UWL 3224	-
BR 3225	19	32	20	23	-	25.2	-	UWL 3225	-
BR 3226	19	32	20	23	-	26.2	-	UWL 3226	-
BR 320024	19	32	20	24	5.9	-	-	-	UL 32-016548
BR 322224	19	32	20	24	-	22.2	-	-	UL 32-0000421
BR 32-01-06	24	32	0	22	5.9	-	-	-	-
M 75100	19	36	22	25	5.9	-	-	F-84174	-
BR 3620	19	36	22	25	-	20.2	-	UW 2136.20	-
M 75222	19	36	22	25	-	20.2	-	UW 2136.20	-
BR 3622	19	36	22	25	-	22.2	-	UW 2136.22	-
BR 3625	19	36	22	25	-	25.2	-	UW 2136.25	-
BR 3626	19	36	22	25	-	26.2	-	UW 2136.26	-
BR 362426	19	36	22	26	-	24.2	-	-	UL 36-0000425
BR 362526	19	36	22	26	-	25.2	-	-	UL 36-0000426
BR 400024	23	40	21	24	5.9	-	-	-	UL 40-0025408
BR 402424	23	40	21	24	-	24.2	-	-	-
BR 4000	23	40	23.5	27	5.9	-	-	UWL 4000	-
BR 4020	23	40	23.5	27	-	20.2	-	FAG No. 10- 4393A	UL 40-0021786
BR 4025	23	40	23.5	27	-	25.2	-	UWL 4025	-
BR 2814.2(22)	14.2	28	10	18	-	22.2	-	-	-
BR 2814.216.623(22)	14.2	28	16.6	23	-	22.2	-	-	UL 28-0959274
BR 2815(06)	15	28	13	16.8	5.9	-	-	-	-
BR 2815(24)	15	28	13	23	-	24.2	-	-	UL 28-0021159
BR 2816	16	28	26	22	-	-	-	-	-
M 75324	16	28	13	17	-	24.2	-	F 94733	-
BR 2816(24)1323	16	28	13	23	-	24.2	-	-	UL 28-0021164
BR 28161620	16	28	16	20	-	-	-	-	-
BR 3015.875	15.875	30	25.4	20	-	-	-	-	-
BR 3016	16	30	26	21	-	-	-	-	-
BR 3017(26)	17	30	19	22	-	26.2	-	-	UL 30-0021106
M 76100	16.2	32	19.75	24	5.9	-	-	-	UL 32-0959261

BR 3216.3(06)	16.3	32	17	20	5.9	-	-	-	UL 32-0023114
BR 3216.3(20)	16.3	32	17	20	-	20.2	-	-	-
BR 3216.5(06)	16.5	32	19	23	5.9	-	-	-	-
BR 3216.5(22)	16.5	32	19	23	-	22.2	-	-	-
BR 3217S	17	32	22	25	-	20.2	-	-	-
BR 3217L	17	32	22	25	-	20.2	-	-	-
BR 3218.5(06)	18.5	32	19	22	5.9	-	-	-	UL 32-0019169
BR 3221(06)	21	32	19	23	5.9	-	-	-	UL 32-0016548
BR 3420	20	34	23	24	-	-	-	-	-
BR 3422	22	34	26	27	-	-	-	-	-
BR 3618.5(06)	18.5	36	19	22	5.9	-	-	-	UL 36-0014782
BR 3621(06)	21	36	22	26	5.9	-	-	FAG No. 10- 4461A	UL 36-0016442
BR 3621(20)	21	36	22	26	-	20.2	-	-	-
M 75400	19	37	25	27	5.9	-	-	F-52364	-
BR 3719(25)26X	19	37	26	26	-	25.2	-	-	-
BR 3719(22)	19	37	25	27	-	22.2	-	-	-
BR 4019(06)	19	40	21	24	5.9	-	-	SUSSEN UZ 401	-
M 75599	19	43	22	29	-	-	-	F-35303	-
BR 450029	25	45	25	29	-	-	-	-	UL 45-0959268
BR 2130(20)	18*	30	0	22	-	20.2	-	RUW 2130.20	-
BR 2134 (25)	22	34	17	27	-	-	-	RUW 2134.25	-
BR 20-3P	20*	32	0	25	-	-	-	-	NTN No. FR 20-3P
BR 28(P)16	16	28	26	22	-	-	3 x 2.5	-	NTN No. FRIS 16 x 28
BR 28(P)16.5	16.5	28	23	22	-	-	3 x 2.5	-	-
BR 28(P)16.5(27)	16.5	28	27	16.8	-	-	2.5 x 2.0	-	-
BR 28(P)16.5(23X)	16.5	28	23	23	-	-	3 x 2.5	-	-
BR 30(P)15.875	15.875	30	25.4	20	-	-	2.5 x 2.5	-	NACHI No. 2 B 15 Z
BR 30(P)16	16	30	26	21	-	-	3 x 2.5	-	-
M 75788	16.5	30	19	22	-	-	3 x 2.5	F-29934	-
BR 32-01-06	24	32	0	22	-	-	2.5 x 2	-	-
BR 31.750(P)18	18	31.75	24	23	-	-	2.5 x 2.5	-	-
M 75888	17	32	25.4	27	-	-	4 x 4	F-22648	-
BR 32(P)18-24	18	32	24	23	-	-	2.5 x 2.5	-	NTN No. FRIS 183224
BR 32(P)18-26	18	32	26	23	-	-	2.5 x 2.5	-	NTN No. FRIS 183226
BR 32(P)19	19	32	20	23	-	-	3 x 2.5	-	NTN No. FRIS 19 x 32
BR 32(P)19.26	19	32	26	23	-	-	3 x 2.5	-	-
M 75900	24	32	0	22	-	-	2.5 x 2.5	-	-
BR 32(P)22**	24	32	0	22	-	-	2.5 x 2.5	F-18636	UL 32-0036128
BR 34(P)18	18	34	21	26	-	-	2.5 x 2.5	-	-
M 76088	19	34	25.4	27	-	-	4 x 4	F-21460	-
BR 34(P)20-26	20	34	26	23	-	-	3 X 2.5	-	-
BR 42(P)25	25	42	26	24	-	-	4 x 4	-	NTN No. FRIS 2542/26 NP
M 75688	25	52	23.5	28	-	-	8.5 x 2.5	F-32664	-
BR 35(P)17 BB	17	35	22	22	-	-	4 x 4.2	SRO 12304	1785154
BR 47(P)17 BB	17	47	22	22	-	-	4 x 4.2	SRO 12280	1785152
BR 17(P)34	17	34	27	30	-	-	4 x 2	-	-
BR 20(P)47	20	47	22	25	-	-	4 x 2.3	-	-
BR 25(P)52	25	52	22	24	-	-	8.5 x	-	-

							2.5	
M 76100	16.2	32	19.7	24	5.5	-	-	-
M 76220	19	36	22	25	-	20.2	-	-
BR 34(P)19-25.4	19	34	25.4	27	-	-	4 x 4	-