



M336900 – LL352100 SERIES


| CONE | | | Max Shaft Fillet Radii R ① | Weight | CUP | | | Max Hs'ng Fillet Radii r ① | Weight | BEARING WIDTH T | Remarks |
|------------------------------|--------------------|------------------|----------------------------|----------------------|---|-------------------|------------|----------------------------|-------------------|-----------------|---|
| Number | BORE d | WIDTH B | | | Number | OUTSIDE DIA D | WIDTH c | | | | |
| M336900 Series (cont) | | | | | | | | | | | |
| M336947 | 177.800 7.0000 | 57.150 2.2500 | 9.7 .38 | 6.70 kg 14.77 lb | | | | | | | |
| M336948 | 178.595 7.0313 | 57.150 2.2500 | 3.3 .13 | 6.66 kg 14.69 lb | | | | | | | |
| M336949 | 179.934 7.0840 | 57.150 2.2500 | 3.3 .13 | 6.50 kg 14.32 lb | | | | | | | |
| *M336949A | 179.388 7.0625 | 60.325 2.3750 | 3.3 .13 | 6.99 kg 15.41 lb | M336949A may be paired with all single cups corresponding to M336946 and will require 3.175 mm (.1250 in) to be added to the T-width values. | | | | | | |
| H337800 Series | | | | | | | | | | | |
| H337840 | 165.087 6.4995 | 87.312 3.4375 | 1.5 .06 | 33.40 kg 73.66 lb | *H337816XDXX 301.700 11.8780 | 196.850 7.7500 | .9 .04 | 25.38 kg 55.96 lb | 190.546 7.5018 | | H337840XX: MADE FROM VACUUM MELT STEEL |
| *H337840XX | 165.087 6.4995 | 87.312 3.4375 | 1.5 .06 | 33.40 kg 73.65 lb | *H337816XD 301.700 11.8780 | 196.850 7.7500 | .9 .04 | 25.38 kg 55.96 lb | 190.546 7.5018 | | H337846XX: MADE FROM VACUUM MELT STEEL |
| H337844 | 174.612 6.8745 | 87.312 3.4375 | 1.5 .06 | 30.01 kg 66.17 lb | | | | | | | H337816XD: SPECIAL CHAMFER ON LEFTFACE OD SPECIAL CHAMFER ON RIGHTFACE OD |
| H337846 | 177.787 6.9995 | 87.312 3.4375 | 1.5 .06 | 28.73 kg 63.36 lb | | | | | | | |
| *H337846XX | 177.787 6.9995 | 87.312 3.4375 | 1.5 .06 | 28.73 kg 63.35 lb | | | | | | | H337816DXX: MADE FROM VACUUM MELT STEEL SPECIAL CHAMFER ON LEFTFACE OD SPECIAL CHAMFER ON RIGHTFACE OD |
| 341000 Series | | | | | | | | | | | |
| EE341048 | 120.650 4.7500 | 59.530 2.3437 | 6.4 .25 | - - | 341096 244.475 9.6250 | 36.512 1.4375 | 3.3 .13 | 3.02 kg 6.66 lb | 57.150 2.2500 | | |
| H343200 Series | | | | | | | | | | | |
| *†JH343249NW | 220.000 8.6614 | 98.000 3.8583 | 3.0 .12 | 18.20 kg 40.14 lb | *†JH343210 340.000 13.3858 | 80.100 3.1535 | 1.5 .06 | 9.70 kg 21.39 lb | 98.100 3.8622 | | JH343249NW: EXTENDED SMALL RIB FRONTFACE CHAMFER SLOTS IN FRONTFACE JH343210: SHOULDER ON OD BACKFACE M348449WS: KEYWAY IN ID FRONTFACE |
| M348400 Series | | | | | | | | | | | |
| M348448WS | 247.650 9.7500 | 63.500 2.5000 | 6.4 .25 | 12.17 kg 26.84 lb | M348410 346.075 13.6250 | 50.800 2.0000 | 6.4 .25 | 5.43 kg 11.97 lb | 63.500 2.5000 | | |
| M348449 | 247.650 9.7500 | 63.500 2.5000 | 6.4 .25 | 12.16 kg 26.82 lb | | | | | | | |
| *M348449WS | 247.650 9.7500 | 63.500 2.5000 | 6.4 .25 | 12.05 kg 26.58 lb | | | | | | | |
| M349500 Series | | | | | | | | | | | |
| *M349546XX | 255.600 10.0630 | 63.500 2.5000 | 1.5 .06 | 10.42 kg 22.97 lb | M349510 342.900 13.5000 | 44.450 1.7500 | 3.3 .13 | 4.01 kg 8.85 lb | 57.150 2.2500 | | M349546XX: MADE FROM VACUUM MELT STEEL |
| M349547 | 255.600 10.0630 | 63.500 2.5000 | 1.5 .06 | 10.42 kg 22.97 lb | *M349510-B 342.900 13.5000 | 44.450 1.7500 | 3.3 .13 | 4.54 kg 10.01 lb | 22.225 .8750 | | M349510-B: FLANGE ON OD FRONTFACE, BEARING WIDTH IS T1 DIMENSION |
| M349549 | 257.175 10.1250 | 57.150 2.2500 | 6.4 .25 | 9.40 kg 20.73 lb | *M349510W 342.900 13.5000 | 44.450 1.7500 | 3.3 .13 | 4.01 kg 8.84 lb | 57.150 2.2500 | | M349510W: KEYWAY IN OD BACKFACE |
| M349549A | 257.175 10.1250 | 57.150 2.2500 | 10.7 .42 | 9.16 kg 20.20 lb | M349511 342.900 13.5000 | 44.450 1.7500 | 3.3 .13 | 4.15 kg 9.15 lb | 57.150 2.2500 | | M349512XX: MADE FROM VACUUM MELT STEEL |
| M349549W | 257.175 10.1250 | 57.150 2.2500 | 6.4 .25 | 9.44 kg 20.82 lb | *M349512XX 342.900 13.5000 | 44.450 1.7500 | 3.3 .13 | 4.15 kg 9.15 lb | 57.150 2.2500 | | |
| 350000 Series | | | | | | | | | | | |
| EE350701 | 177.800 7.0000 | 95.250 3.7500 | 6.4 .25 | - - | 351687 428.625 16.8750 | 61.912 2.4375 | 6.4 .25 | 22.52 kg 49.65 lb | 106.362 4.1875 | | |
| EE350750 | 190.500 7.5000 | 95.250 3.7500 | 6.4 .25 | - - | 351687V 428.625 16.8750 | 61.912 2.4375 | 6.4 .25 | 22.52 kg 49.65 lb | 106.362 4.1875 | | |
| EE350750V | 190.500 7.5000 | 95.250 3.7500 | 6.4 .25 | - - | | | | | | | |
| LL352100 Series | | | | | | | | | | | |
| LL352148 | 279.400 11.0000 | 22.860 .9000 | 1.5 .06 | 1.76 kg 3.88 lb | LL352110 317.500 12.5000 | 18.288 .7200 | 1.5 .06 | .74 kg 1.64 lb | 22.860 .9000 | | |
| | | | | | LL352111 317.500 12.5000 | 17.653 .6950 | 1.5 .06 | .71 kg 1.56 lb | 22.225 .8750 | | |
| LL352149 | 279.400 11.0000 | 24.384 .9600 | 1.5 .06 | 1.85 kg 4.08 lb | LL352149 may be paired with all single cups corresponding to LL352148 and will require 1.524 mm (.0600 in) to be added to the T-width values. | | | | | | |




SINGLE ROW



SINGLE ROW WITH FLANGE



DOUBLE CONE



DOUBLE CUP

8